


醫用工具及配件系列 (皮质骨成型钻)
 Medical tools and parts series (Cortical countersink)
 医療器具及び部品シリーズ (皮质骨成型ドリル)


(超防锈高耐磨 (AA) & 高精度特殊非標成型)
 (ultra-high anti-rust(AA) & high precision special nonstandard forming)
 超防锈高耐磨耗 (AA) & 高精度特殊非標準成型



★、可以任意CAD/3D/實物結構方式的倒角加工。
 Chamfering process for any structural style
 of CAD/3D/entity

部分尺寸 some sizes



	刃徑 ϕD Diameter	2.7	3.1	3.7	3.9	4.2	5.0
	刃徑 $\phi D1$ Diameter	3.6	4.0	4.5	5.0	6.0	7.0
	刃長 $L1$ Length of cut 刃の長さ	5.5	5.5	5.5	5.5	7.5	7.2
	柄徑 ϕd Shank Dia.	2.35	2.35	2.35	2.35	2.35	2.35
	總長 L Overall length 總長さ	28	28	28	28	27	27
	刃數 Z No. of flute	5	5	5	5	5	5



※ 必要可帶穿透&不穿透，不同等級加工的中空、空芯內孔加工。

With or without penetration, hollow & hollow core inner hole process with different grades.
 必要に応じて、貫通付き&貫通なし、各レベル加工での中空、中空内穴加工。

★可超硬、超精研磨。任意的柄部類型、芯厚、容屑槽寬度、刃背方式、鑽尖方式、內冷卻孔方式、刃部結構、刃口角度、刃口鋒利程度之要求。及高可至 $\pm 0.003\text{mm}$ ($3\mu\text{m}$) 的尺寸公差要求 We can produce with super hard and super finish grinding and satisfy your requirement of any type of shank, web thickness, width of chip flute, land, drill tip, inner cooling hole, structure of cutting edge, angle of cutting edge, degree of sharpness of cutting edge, and the dimension tolerance can be up to $\pm 0.003\text{mm}$ ($3\mu\text{m}$)